




LUMIPLUS ESSENTIAL PAR56 LAMP



WHITE 73761 	Consumption	14,5 W (20 VA)
	Luminous flux	1.485 lm
	Rated Voltage	12 V AC
IP68. Cable not included. Must always be installed submerged in water.		
RGB 75767 	Consumption	22 W (29 VA)
	Luminous flux	1.100 lm
	Rated Voltage	12 V AC
IP68. Cable not included. Can be only controlled by a normally closed push button. Must always be installed submerged in water.		

VOLTAGE:	12 V AC
FREQUENCY:	50/60 Hz
SERVICE LIFE:	L70-50,000 h
MAX. WATER TEMPERATURE:	40 °C
MAX. INSTALLATION DEPTH:	2 m
MAXIMUM WATER TREATMENT VALUES:	Chlorine: 2 mg/l Bromine: 5 mg/l Salt chlorinator (NaCl): 6 g/l Pool water pH: 7.2 and 7.6
ACCESSORIES & COMPATIBLE NICHES:	Compatible with any PAR56 projector
MATERIALS:	Polyamide



PACKAGING AND PALLETIZATION

Volume/Single box (m ³)	0.003
Weight/Single box (kg)	0.540
Units/Standard box	6
Volume/Standard box (m ³)	0.028
Weight/Standard box (kg)	2,8
Units/Pallet	72
Volume/Pallet (m ³)	2.2
Weight/Pallet (kg)	180

