



Floculante sólido en Cartuchos / en Saquitos

Floculación continua para agua cristalina

Producto de acción coagulante y floculante, su sola aplicación, elimina las partículas en suspensión, mejorando la transparencia del agua en la piscina.

PROPIEDADES

Aspecto	Sólido
Color.....	Blanco crema
Disolución en el skimmer a 28°C	2 ciclos completos de filtración
pH de una solución al 1%.....	3,6
Composición.....	Sulfato de aluminio

CARACTERÍSTICAS

Los Floculantes sólidos en cartucho o saquito tienen la propiedad de formar flóculo en el agua a la entrada del filtro, estos flóculos se depositan en la superficie de la carga filtrante reteniendo a su paso todas las partículas en suspensión que se encuentran en el agua de la piscina. Con el siguiente lavado del filtro, las impurezas se eliminan definitivamente.

DOSIFICACIÓN

Piscinas de	10 a 50 m ³ :	1 cartucho o saquito cada 10 días
Piscinas de	50 a 100 m ³ :	2 cartuchos o saquito cada 10 días
Piscinas de	100 a 150 m ³ :	3 cartuchos o saquito cada 10 días

Estas dosis son de carácter orientativo y pueden ser modificadas en función de la turbidez del agua.

MODO DE EMPLEO

Colocar las unidades necesarias en el interior de los cestos de los skimmers, después de haber efectuado un lavado en el equipo de filtración.

INFORMACIÓN PARA LA SEGURIDAD DEL USUARIO

- Manténgase fuera del alcance de los niños.
- Nocivo por ingestión.
- Irrita los ojos.
- Usar protección para los ojos/la cara.

EN CASO DE ACCIDENTE O MALESTAR, ACUDA INMEDIATAMENTE AL MÉDICO.
(Si es posible muéstrele la etiqueta).

La información contenida en este folleto es según nuestro criterio correcta. No obstante, como las condiciones en las que se usan estos productos caen fuera de nuestro control, no podemos responsabilizarnos de las consecuencias de su mala utilización.

FLOCULANT IN CARTRIDGES

11390

Product with coagulating properties. The use of it eliminates particles in suspension thus improving the transparency of the water.

PROPERTIES

Appearance	Solid
Colour	Creamy – white
Dissolution in a skimmer at 28 ° C.	2 complete cycle of filtration
pH (1% solution)	3.6

CHARACTERISTICS

11390 cartridges from floccules in the water mouth of the filter; these floccules are deposited on the surface of the filtering media holding back all the suspended particles found in the pool water.

DOSAGE

Pools of 10 to 50 m³: 1 tablet of 11390 every 10 days.
Pools of 50 to 100 m³: 2 tablets of 11390 every 10 days.
Pools of 100 to 150 m³: 3 tablets of 11390 every 10 days.

These doses are merely meant as a guideline and may be modified depending on the turbidity of the water.

INSTRUCTIONS FOR USE

Place the relevant number of 11390 cartridges in the skimmers baskets, once the filtering equipment has been backwashed.

PRESENTATION

10 units packed with individual bags in 1 Kg. boxes.

SAFETY PRECAUTIONS:

- Keep the container sealed in a dry place, away from heat and out of the reach of children.
- Should the product be swallowed or brought into contact with the eyes, visit a doctor immediately.



- Do not mix it with other chemical compounds.

IN CASE OF AN ACCIDENT OR DISCOMFORT, CONSULT A DOCTOR IMMEDIATELY (showing him/her the label, if possible).

The information contained in this page is accurate when the correct procedures are followed. We hold no responsibility for misuse of the product.